

**PURCHASE ENQUIRY**

**PURCHASE ENQUIRY NO (S&P)/EL/EE(LT/18-19/81**

**DATE : 25/06/2018**

Sir,  
Please send your quotation/offer with terms and conditions for the materials specified in the table below

Sl No	Item Code	Item Name/Specification	Unit	Required Quantity
1	1415020496	<b>4A, FGN HRC FUSE LINK</b> 4A NS TYPE HBC FUSE LINK RATING: 4A, BREAKING CAPACITY: 80KA, PART NUMBER: NS4, CODE: 401242, MAXIMUM VOLTAGE RATING: 440V, PRE-ARCING-7.2A2SEC, TOTAL I2t- 30A2SEC at 415V, TOTAL I2t- 33A2SEC at 440V	NUMBERS	<b>100</b>
2	1415020682	<b>6A - FGN HRC FUSE LINK.</b> 6A NS TYPE HBC FUSE LINK RATING: 6A, BREAKING CAPACITY: 80KA, PART NUMBER: NS6, CODE: 401243, MAXIMUM VOLTAGE RATING: 440V, PRE-ARCING -22A2SEC, TOTAL I2t- 92A2SEC at 415V, TOTAL I2t- 100A2SEC at 440V, MAKE:GE/EE	NUMBERS	<b>100</b>
3	1415021093	<b>HRC FUSE 16A NS16</b> CLIP-ON TYPE HRC FUSE LINK WITH STAGGERED TAGS BS SIZE: F1, TAG TYPE: CLIP-ON STAGGERED TAG, RATED CURRENT: 16A, RATED VOLTAGE: 415 V AC, BREAKING CAPACITY: 80kA, STANDARDS/APPROVALS: BS88 / IEC60269 / IS 13703, CODE: 401235, MAXIMUM VOLTAGE RATING: 440V, PRE-ARCING -200A2SEC, TOTAL I2t- 800A2SEC at 415V, TOTAL I2t- 950A2SEC at 440V, MODEL: NS16, MAKE: EATON / BUSSMANN / GE / SIEMENS / L&T / STANDARD	NUMBERS	<b>150</b>
4	1415021107	<b>20A - FGN HRC FUSE LINKS.</b> 20A NS TYPE HBC FUSE LINK RATING: 20A, BREAKING CAPACITY: 80KA, PART NUMBER: NS20, CODE: 401237, MAXIMUM VOLTAGE RATING: 440V, PRE-ARCING-360A2SEC, TOTAL I2t- 1200A2SEC at 415V, TOTAL I2t- 1500A2SEC at 440V, MAKE:GE/EE	NUMBERS	<b>25</b>
5	1415023291	<b>HRC FUSES 10A NS10</b> 10A NS TYPE HBC FUSE LINK RATING: 10A, BREAKING CAPACITY: 80KA, PART NUMBER: NS10, CODE: 401234, MAXIMUM VOLTAGE RATING: 440V, PRE-ARCING -170A2SEC, TOTAL I2t- 650A2SEC at 415V, TOTAL I2t- 700A2SEC at 440V, MAKE:GE/EE	NUMBERS	<b>50</b>
6	1415052380	<b>6AMPS DRUM TYPE FUSE</b> HF series cylindrical fuse link Rating :6A, Breaking capacity :80KA, Suitable for FN32/63/FNX32/63 S-D-F & for HCO 32 fuse base, Voltage :415V, Size:14x51/cylindrical/drum type, CAT No.:SF90146, WATT Loss limit as per IS 13703:5W, Rated watt loss:1.1W, Make: L&T/BUSSMANN	NUMBERS	<b>300</b>
7	1425021695	<b>HRC FUSE LINKE 63 AMP</b> 63A NS TYPE HBC FUSE LINK RATING: 63A, BREAKING CAPACITY: 80KA, PART NUMBER: ES63, CODE: 401188, MAXIMUM VOLTAGE RATING: 440V, PRE-ARCING -5400A2SEC, TOTAL I2t- 14500A2SEC at 415V, TOTAL I2t- 25000A2SEC at 440V, MAKE:GE/EE	NUMBERS	<b>100</b>
8	1425071293	<b>HF FUSE 14X51 32A 440V 80KA</b> HF series cylindrical fuse link Rating :32A, Breaking capacity :80KA, Suitable for FN32/63/FNX32/63 S-D-F & for HCO 32 fuse base, Voltage :415V, Size:14x51/cylindrical/drum type, CAT	NUMBERS	<b>300</b>

**PURCHASE ENQUIRY**

**PURCHASE ENQUIRY NO:SE(S&P)/EL/EE(LT/18-19/81**

**DATE : 25/06/2018**

Sl No	Item Code	Item Name/Specification	Unit	Required Quantity
		No.:SF90142, WATT Loss limit as per IS 13703: 5W, Rated watt loss:5W, Make: L&T/BUSSMANN		
9	1425071692	<b>HF FUSE 14X51 63AMPS 440V80KA.</b> HF series cylindrical fuse link Rating :63A, Breaking capacity :80KA, Suitable for FN63/FNX63 S-D-F & for HCO 63 fuse base, Voltage :415V, Size:14x51/cylindrical/drum type, CAT No.:SF90159, WATT Loss limit as per IS 13703: 7W, Rated watt loss:7.4, Make: L&T/BUSSMANN	NUMBERS	300
10	1425100706	<b>8A CYLINDRICAL HRC FUSE</b> HF series cylindrical fuse link Rating :8A, Breaking capacity :80KA, Suitable for FN32/63/FNX32/63 S-D-F & for HCO 32 fuse base, Voltage :415V, Size:14x51/cylindrical/drum type, CAT No.:SF90147, WATT Loss limit as per IS 13703: 5W, Rated watt loss:1.2W, Make: L&T/BUSSMANN	NUMBERS	50
11	1425100803	<b>10A CYLINDRICAL HRC FUSE</b> HF series cylindrical fuse link Rating :10A, Breaking capacity :80KA, Suitable for FN32/63/FNX32/63 S-D-F & for HCO 32 fuse base, Voltage :415V, Size:14x51/cylindrical/drum type, CAT No.:SF90148, WATT Loss limit as per IS 13703: 5W, Rated watt loss:1.0, Make: L&T/BUSSMANN	NUMBERS	100
12	1425101001	<b>16A CYLINDRICAL HRC FUSE</b> HF series cylindrical fuse link Rating :16A, Breaking capacity :80KA, Suitable for FN32/63/FNX32/63 S-D-F & for HCO 32 fuse base, Voltage :415V, Size:14x51/cylindrical/drum type, CAT No.:SF90150, WATT Loss limit as per IS 13703: 5W, Rated watt loss:2.4W, Make: L&T/BUSSMANN	NUMBERS	300
13	1425101109	<b>20A CYLINDRICAL HRC FUSE</b> HF series cylindrical fuse link Rating :20A, Breaking capacity :80KA, Suitable for FN32/63/FNX32/63 S-D-F & for HCO 32 fuse base, Voltage :415V, Size:14x51/cylindrical/drum type, CAT No.:SF90151, WATT Loss limit as per IS 13703: 5W, Rated watt loss:2.4W, Make: L&T/BUSSMANN	NUMBERS	50
14	1425101401	<b>40A CYLINDRICAL HRC FUSE</b> HF series cylindrical fuse link Rating :40A, Breaking capacity :80KA, Suitable for FN63/FNX63 S-D-F & for HCO 63 fuse base, Voltage :415V, Size:14x51/cylindrical/drum type, CAT No.:SF90143, WATT Loss limit as per IS 13703: 7W, Rated watt loss:5W, Make: L&T/BUSSMANN	NUMBERS	25
15	1425101508	<b>50A CYLINDRICAL HRC FUSE</b> HF series cylindrical fuse link Rating :50A, Breaking capacity :80KA, Suitable for FN63/FNX63 S-D-F & for HCO 63 fuse base, Voltage :415V, Size:14x51/cylindrical/drum type, CAT No.:SF90158, WATT Loss limit as per IS 13703: 7W, Rated watt loss:5W, Make: L&T/BUSSMANN	NUMBERS	25
16	1425140295	<b>HRC NS TYPE FUSE 2A</b> 2A NS TYPE HBC FUSE LINK RATING: 2A, BREAKING CAPACITY: 80KA, PART NUMBER: NS2, CODE: 401236, MAXIMUM VOLTAGE RATING: 440V, PRE-ARCING -2.2A2SEC, TOTAL I2t- 9.5A2SEC at 415V, TOTAL I2t- 11A2SEC at 440V, MAKE:GE/EE	NUMBERS	100

**PURCHASE ENQUIRY**

**PURCHASE ENQUIRY NO:SE(S&P)/EL/EE/LT/18-19/81**

**DATE : 25/06/2018**

Sl No	Item Code	Item Name/Specification	Unit	Required Quantity
17	1425141399	32A NS TYPE FUSE 32A NS TYPE HBC FUSE LINK RATING: 32A, BREAKING CAPACITY: 80KA, PART NUMBER: NS32, CODE: 401239, MAXIMUM VOLTAGE RATING: 440V, PRE-ARCING -600A2SEC, TOTAL I2t- 3500A2SEC at 415V, TOTAL I2t- 4050A2SEC at 440V, MAKE:GE/EE	NUMBERS	150
18	1425220299	2A DRUM TYPE FUSE Type HF series cylindrical fuse link Rating :2A, Breaking capacity :80KA, Suitable for FN32/63/FNX32/63 S-D-F & for HCO 32 fuse base, Voltage :415V, Size:14x51/cylindrical/drum type, CAT No.:SF90144, WATT Loss limit as per IS 13703:5W, Rated watt loss:0.6W, Make: L&T/BUSSMANN	NUMBERS	300
19	1425220493	4A DRUM TYPE FUSE HF series cylindrical fuse link Rating :4A, Breaking capacity :80KA, Suitable for FN32/63/FNX32/63 S-D-F & for HCO 32 fuse base, Voltage :415V, Size:14x51/cylindrical/drum type, CAT No.:SF90145, WATT Loss limit as per IS 13703:5W, Rated watt loss:0.6W, Make: L&T/BUSSMANN	NUMBERS	300

**Important Dates:**

- 1 . Last date for receipt of quotations/tenders/offers : **24/07/2018 17:30**
- 2 . Opening Date of quotations/tenders/offers : **25/07/2018 16:00**

**Important Note:**

1. Quotations/Tenders/Offers shall be in a sealed cover with following superscription.
  - a) Purchase Enquiry Number and Date .
  - b) Date of opening
2. Bidders/Agencies shall invariably furnish valid GSTIN along with Quotations/Offers.(With Valid HSN/SAC Codes)
3. Offers without valid GSTIN & HSN Codes will not be considered for evaluation.
4. Bidders/Agencies shall mention their deviation from Terms & Conditions of enquiry along with quotation/offer, if not, it will be treated as accepted in entirety.

**Terms and Conditions of Enquiry:**

- 1 VALIDITY : The rates offered shall be valid for a period of 180 days from the date fixed for receipt of tender/quotation.
- 2 PRICES : The price shall be quoted per Unit exclusive of Taxes and duties. The following components of the rates shall also be mentioned. a) F.O.R , b) Discount if any, c) Applicable IGST/SGST/CGST d) HSN Code , f) Freight , g) Any other charges.
- 3 TERMS OF PAYMENT : 100% Payment with full taxes & duties as per actuals after receipt and acceptance of materials at site. If any other mode of payment is insisted/mentioned by the supplier, corporation reserves the right of loading the additional cost to arrive at the landed cost which may please be noted.
- 4 QUANTITY : The quantity mentioned in the enquiry is subjected to variation depending on the final requirements and Purchase order condition.
- 5 GUARANTEE / WARRANTY : The materials shall be guaranteed for a period of 12 months from the date of commissioning or 18 months from the date of dispatch whichever is earlier against manufacturing defects/bad workmanship. During this period any defects noticed shall be replaced free of cost at site without waiting for settlement of claims.

**PURCHASE ENQUIRY**

**PURCHASE ENQUIRY NO (S&P)/EL/EE/LT/18-19/81**

**DATE : 25/06/2018**

- 6 PENALTY : For delay in delivery of material beyond the stipulated delivery period, penalty @ 0.5 % per week subject to a maximum of 5% of value of the delayed quantity shall be applicable.
- 7 QUALITY : If the materials supplied are found to be substandard, the materials will be rejected and action will be taken as per conditions of purchase order. Materials should be made of best quality in accordance with the specification duly indicating IS Code, Make , Brand etc.
- 8 DEALERSHIP CERTIFICATE : Copy of valid dealership certificate shall be enclosed wherever applicable.
- 9 TRANSPORT : Material Shall be insured & transported only through reputed transporters who have godown at Raichur/Yeramarus Like Associated Road Carriers, TCI, SER etc.
- 10 EARNEST MONEY DEPOSIT : If the quoted value is more than Rs. 50000.00(Fifty Thousand Only) then 1% of the quoted value shall be furnished in the form of DD/BG drawn in favour of General Manager (Finance), YTPS,Raichur Power Corporation Limited, Yeramarus - 584 134, from any nationlised / Scheduled Bank with minimum validity of 3(Three) months in a seperat sealed cover. Exemption Certificate for EMD/SD issued by NSIC or By any State Govt or Central Govt will not be considered and such offers are liable for rejection.
- 11 AGREEMENT : An agreement shall be executed by the supplier ( as per RPCL format) immediately after receipt and acceptance of Purchase Order on e-stamped duty paper Worth of Rs 200.00 .(Purchased in Karnataka Only) before effecting supply. However in case any supplies are made the payment will be released only after entering into agreement. E.M.D. will be forfeited if the supplier fails to supply the materials after acceptance / placing of purchase order.
- 12 SECURITY DEPOSIT : If the landing cost of the Purchase order exceeds Rs. 50000.00(Fifty Thousand), then 10 % of the landing cost shall be furnished as SD in the form of DD or BG issued from any Nationalised/Scheduled Bank and it shall be valid for the entire contract/guarantee period before effecting the supply.
- 13 JURISDICTION: Law courts of Raichur.

Yours Faithfully

For KARNATAKA POWER CORPORATION LIMITED

SUPERINTENDING ENGINEER(STORES &  
PURCHASE)  
YERMARUS THERMAL POWER STATION, RPCL  
YERMARUS, PIN-584134  
Phone 9480830561 Fax 8532286003  
Mail